Gafast Pigment Yellow 151

Chemical Class : Benzimidazolone

: Pigment Yellow 151

C.I. No. : 13980

Greenish yellow pigment with excellent fastness to light & weathering. Mainly suitable for Automotive paints, Printing

Inks, Plastic Coloration.

Chemical Structure:

Powder



Full Shade

Product specification:

Physical Data: Physical form

C.I.Name

Specific Surface Area (BET), (m^2/g) 11 – 13 Average Particle size, (μm) $\cong 0.239$ Oil Absorption Value, (g/100g) 45.56 pH of 10% extract 6.0 – 8.0



Reduction 1:16 TiO₂

Resistance to Solvents:

 Water
 5

 Mineral Turpentine oil
 5

 n-Butanol
 5

 Xylene
 4 - 5

 Butyl Acetate
 5

 MEK
 4 - 5

Heat Stability: 240°C


Weather fastness:

Full shade Reduction
Alkyd/melamine 4 - 5 4 - 5
Acrylic/melamine 4 - 5 4 - 5
Air-drying Alkyd 4 - 5 4 - 5

Fastness to Over coating: 5

Suitability For: (+ = Suitable, 0 = Not Suitable)
Baking system +

Acrylic-isocyanate system +
Acid curing systems 0
Amine curing systems 0
Air drying systems +



PY151 X Ray Diffraction Plot

50000

40000

10000

20000

10000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000

20000


20000


20000

20000

Reflectance Curve (Stoving Paint) Full shade (5%) & Reduction (1:16)

X-ray Diffractogram





Transmission Electron Micrograph (TEM)

Particle Size Distribution

Note:

Information given in this technical data sheet is based on current knowledge and our laboratory evaluation; it is presented as our opinion without any guarantee. Buyers must carry out their own tests and experiments to determine the suitability and completeness of our products for their use and application.